

Series	Description	Size Testd WxH [in]	Perfor. Grade [PG]	Design Pressure [DP]	Water Resistance Pressure	Canadian Air Leakage	Class
3000 Slider	Fixed	95 x 60	55	+/- 2640 Pa	730 Pa	Fixed	CW
	Fixed	56 x 56	75	+/- 3600 Pa	730 Pa	Fixed	LC
	Vert. Slider	73 x 73	45	+/- 2280 Pa	400 Pa	A3	LC
	Vert. Slider	41 x 63	70	+/- 3360 Pa	400 Pa	A3	LC
	Horiz. Slider	71 x 56	40	+/- 1920 Pa	400 Pa	A3	LC
	Combination	97 x 67	40	+/- 1920 Pa	330 Pa	A3	LC
	Combination	96 x 72	25	+/- 1200 Pa	440 Pa	A3	LC
	Combination	73 x 85	45	+/- 2280 Pa	400 Pa	A3	LC
4000 Csmt & Awning	Fixed	71 x 71	55	+/- 2640 Pa	730 Pa	Fixed	CW
	Fixed	56 x 56	75	+/- 3600 Pa	730 Pa	Fixed	LC
	Csmt. - Roto	32 x 63	75	+/- 3600 Pa	730 Pa	A3	CW
	Csmt. - Cam	32 x 63	75	+/- 3600 Pa	730 Pa	A3	CW
	Awning. - Roto	48 x 40	55	+/- 2640 Pa	730 Pa	A3	CW
	Awning - Cam	48 x 40	55	+/- 2640 Pa	730 Pa	A3	CW
	Combination	96 x 73	35	+/- 1440 Pa	730 Pa	A3	LC
	Combination	73 x 73	45	+/- 2160 Pa	720 Pa	A3	LC
	Combination	49 x 108	45	+/- 2280 Pa	730 Pa	A3	CW
6000 Alum	Casement	32 x 63	45	+/- 2160 Pa	720 Pa	A3	R
	Awning	48 x 40	55	+/- 2640 Pa	720 Pa	A3	R
	Combination	73 x 97	30	+/- 1440 Pa	220 Pa	A3	LC
	Combination	48 x 108	45	+/- 2160 Pa	330 Pa	A3	R